



SAFE & VAULT MANUFACTURERS

# PREMIER HIGH SECURITY SAFE

TDR TORCH & DRILL RESISTING

EQUIVALENT TO  USA: UL TRTL-60  EU: ABIS GRADE 4



MODEL PR3



**TDR torch and drill resisting**



Premier High Security Safe TDR suggested insurable cash rating in unsupported (no alarms) situation is **\$250,000**.



Premier High Security Safe TDR designed to be **fire resisting for one hour**



**MADE IN AUSTRALIA**



# PREMIER HIGH SECURITY SAFE

TDR TORCH & DRILL RESISTING

EQUIVALENT TO USA: UL TRTL-60 EU: ABIS GRADE 4

SAFE & VAULT MANUFACTURERS

**BODY:** The body gives a minimum thickness of 80mm of high density refractory materials at all points. These materials are bonded between inner and outer walls of specially reinforced steel, becoming a complete monolith after pouring. The engagement of the door and body effectively result in a continuous cube of exceptional strength and security.

**DOOR:** The door of the Premier safe has an overall thickness of 135mm, and the 55mm thick defensive slab section contains metals highly resistant to drills and abrasive grinders in addition to the highstrength poured barrier materials and other defences. The lockcase forms an integral part of the entire door structure, giving additional strength.

**BOLTWORK:** Heavy 32mm bolts provide 4 way locking into reinforced sections of the 2 sides, top and bottom of the safe body.

**MOUNTING:** 2 x 20mm recessed bolt holes in base of safe.

**HINGING:** Fully adjustable antijacking hinges, available in standard right hand or optional left hand hinging.

**SHELVING:** All models come standard with 2 x adjustable shelves.

**RE-LOCKER:** Glass operated re-locker.

**LOCKS:** All models available with key, dial combination or digital locking at no extra cost.



MODEL PR3  
Drawer unit optional extra

## RESISTING TO

- Oxy-Acetylene attack
- Explosives and force
- Drills and abrasive grinders
- Pneumatic tools
- Hydraulic tools

| Model       | Height mm |          | Width mm |          | Depth mm |          | Weight | Litres | Locking Points |
|-------------|-----------|----------|----------|----------|----------|----------|--------|--------|----------------|
|             | External  | Internal | External | Internal | External | Internal |        |        |                |
| <b>PRA</b>  | 510       | 355      | 435      | 280      | 435      | 225      | 210kg  | 22     | 4              |
| <b>PRB</b>  | 615       | 460      | 460      | 300      | 510      | 285      | 308kg  | 39     | 4              |
| <b>PR1</b>  | 660       | 508      | 560      | 405      | 560      | 330      | 372kg  | 68     | 8              |
| <b>PR2</b>  | 770       | 610      | 610      | 460      | 660      | 435      | 500kg  | 120    | 8              |
| <b>PR3</b>  | 915       | 762      | 610      | 460      | 660      | 435      | 568kg  | 150    | 8              |
| <b>PR4</b>  | 1070      | 910      | 660      | 508      | 660      | 435      | 704kg  | 195    | 10             |
| <b>PR5</b>  | 1070      | 910      | 765      | 610      | 850      | 585      | 926kg  | 321    | 10             |
| <b>PR6</b>  | 1220      | 1065     | 765      | 610      | 850      | 585      | 1026kg | 375    | 10             |
| <b>PR7</b>  | 1370      | 1219     | 765      | 610      | 850      | 585      | 1128kg | 428    | 12             |
| <b>PR8</b>  | 1525      | 1372     | 765      | 610      | 850      | 585      | 1230kg | 484    | 12             |
| <b>PR9</b>  | 1675      | 1524     | 765      | 610      | 850      | 585      | 1345kg | 537    | 12             |
| <b>PR10</b> | 1835      | 1678     | 765      | 610      | 850      | 585      | 1464kg | 590    | 12             |

### IMPORTANT

Allow 55mm projection for handle on depth measurement.



**ALL CMI SAFES COME WITH A FIVE YEAR WARRANTY, EXCLUDING FREIGHT AND TRAVELLING, WITH A 24 MONTH WARRANTY ON LOCKS.**

CMI Safe Co

ABN | 35 664 874 766

02 9547 1488

sales@cmisafe.com.au

244 West St | Carlton | NSW | 2218

www.cmisafe.com.au



# MADE IN AUSTRALIA

CD DZ 00312 071124